



*Still Built
in the USA...*



DRINKING WATER
NSF/ANSI 61 & 372

VJ

60 HZ VERTICAL JET PUMPS DEEP WELL



FEATURES

High Capacity: Specifically designed to deliver water at high capacities.

Easy to Service: Can be taken apart for service by removal of four bolts. Pipes do not have to be disturbed when service is required.

Powered for Continuous Operation: Pump is designed for continuous operation. All ratings are within the motor manufacturer's recommended working limits.

Corrosion-Resistant: Electrocoat paint process is applied inside and out and then baked on.

Adjustable Automatic Pressure Control Valve:

Guarantees maximum capacity at all times. By-pass check valve equalizes pressure in entire system and helps prevent loss of prime.

Easy to Prime: The VJ series incorporates a vent at the highest point of the casing, including the mechanical seal chamber, for a more thorough air purging, and fast, efficient priming.

NSF Listed: The first NSF listed jet pumps in the industry. All jet pumps and shallow well components only, deep well components are not listed.

APPLICATIONS

Specifically designed for:

- Homes
- Farms
- Cottages

SPECIFICATIONS

Pump

Pipe connection:

1" NPT drive (pressure)

1 ¼" NPT suction

1" NPT discharge.

Pressure switch: AS4, preset (30-50 PSI).

Motor

- NEMA standard.
- ½-1 HP, 115/230 V, 60 Hz, capacitor start.
- Single phase, 3500 RPM.
- Built-in overload with automatic reset.
- Stainless steel shaft.
- Rotation: clockwise when viewed from motor end.

Maximum temperature: 140° F

REQUIRED SYSTEM COMPONENTS

- **Basic Pump Unit:** Includes pump, motor, pressure switch, tubing, fittings, pressure gauge, bushing and pressure control valve (AV21).
- **Deep Well Jet Assembly Package:** Twin Pipe includes: Jet body, nozzle, venturi and foot valve. Packer includes: Jet body with built-in check valve, nozzle and venturi. See Performance Charts on following pages for Jet Assembly package order numbers.

ADDITIONAL ACCESSORIES REQUIRED

For Packer: well casing adapter AWD2 (2") or AWD3 (3"). Must be ordered separately.

AGENCY LISTINGS



Canadian Standards Association




Underwriters Laboratories®



DRINKING WATER
NSF/ANSI 61 & 372

COMPONENTS

Item No.	Description
1	Mechanical seal
2	Impeller
3	Diffuser (Guidevane)
4	Pressure control valve
5	Motor adapter
6	Casing
7	Stainless steel shaft
8	Pressure switch



DIMENSIONS AND WEIGHTS

HP/Model	½-VJ05	¾-VJ07	1-VJ10
Weight	50	53	56
Length	12¾		
Width	12¾		
Height	13½	14¼	14¾

Pressure control valve not included in dimensions. (All dimensions are in inches and weights in lbs. Do not use for construction purposes.)

MODEL INFORMATION

CSA Listed Order No.	U.L. Listed (Indoor use) ^① Order No.	HP
VJ05	VJ05UL	½
VJ07	VJ07UL	¾
VJ10	VJ10UL	1

PERFORMANCE RATINGS - TWIN PIPE SYSTEMS

HP/Model		½ HP-VJ05		¾ HP-VJ07			1HP-VJ10		
Well Casing Min. I.D. (In.)		4							
Pressure Suction	Pipe Size In.	1							
		1¼							
Jet Assembly Package ①		FT4-46	FT4-08	FT4-47	FT4-46	FT4-06	FT4-14	FT4-09	
Jet Body (only)		AT4							
Nozzle		AN014	AN015	AN013	AN014		AN017	AN015	
Venturi		AD722	AD720	AD724	AD722	AD720	AD729	AD721	
Control Valve Setting (PSI) ②		23		34			40	34	36
Feet		Gallons per Minute 30-50 Pressure Switch Setting							
Depth to Jet Assembly (based on submergence of 5 feet)	30	12.2		15.2			18.8		
	40	11.7		13.2			16.7		
	50	10.0		11.7			15.0		
	60	8.2	8.3	9.7	10.0		12.7		
	70		5.8		8.3		10.0		
	80		5.0		7.1		7.9		
	90		3.8		5.8	5.8	5.3	5.8	
	100					5.0		5.0	
	110					3.8		4.6	
	120							3.3	

NOTE: An offset of 50 feet will result in a decrease of about 25% from ratings as shown.

① Jet assembly package includes jet body (AT4), venturi, nozzle and foot valve.

② Deep well jet pumps require a pressure control device on the discharge to provide back pressure to the jet assembly. Failure to control the amount of discharge by adjusting the back pressure (pressure control valve setting) will cause the pump to lose prime. The AV21 measures the pressure on the outbound side so that the high pressure does not open the 30-50 psi switch and turn the pump off.

PERFORMANCE RATINGS - PACKER SYSTEM

HP/Model		½ HP-VJ05				¾ HP-VJ07				1HP-VJ10					
Well Casing (In.)		2		3		2		3		2		3			
Suction	Pipe Size In.	1¼		1½		1¼		1½		1¼		1½			
Jet Assembly Package ①		FP2-38	FP2-08	FP3-42	FP3-09	FP2-50	FP2-47	FP2-09	FP3-40	FP3-43	FP2-48	FP2-43	FP2-08	FP3-40	FP3-49
Jet Body (only)		AP2		AP3		AP2		AP3		AP2		AP3			
Nozzle		AN014	AN015	AN014	AN016	AN013	AN015		AN013	AN014	AN016		AN015		
Venturi		AD722	AD720	AD722	AD721	AD724	AD723	AD721	AD724	AD721	AD729	AD725	AD720	AD724	AD723
Control Valve ② Setting (PSI)		23				34				36			34	36	
Feet		Gallons per Minute 30-50 Pressure Switch Setting													
Depth to Jet Assembly (based on submergence of 5 feet)	30	12.2		12.5		15.2			15.8		18.8			18.8	
	40	10.8		11.3		13.2			13.7		16.7			16.7	
	50	9.0		10.0		11.3			11.7		14.2			15.0	
	60	7.5	7.7	8.2	8.3	9.3	10.3		10.0	10.3	11.7	11.0		12.5	
	70		5.5		6.8		8.7			9.6		9.3		10.0	
	80		4.6		5.8		6.8			8.2		7.7		8.3	
	90		3.4		4.3		5.3			6.7		5.7		6.3	6.5
	100				3.5		4.0	4.2		5.4		4.6	4.6		5.8
	110							3.3		4.3			3.3		5.0
	120							2.3		3.3			2.9		4.2
	130									2.9					3.3
140														2.9	

NOTE: An offset of 50 feet will result in a decrease of about 25% from ratings as shown. Special turned (diameter) couplings are required on 2" packer systems, order no. 64655 in Jet and Sub price book.

① Jet Assembly Package includes jet body, AP2 or AP3; built-in check valve, nozzle and venturi.

② Deep well jet pumps require a pressure control device on the discharge to provide back pressure to the jet assembly. Failure to control the amount of discharge by adjusting the back pressure (pressure control valve setting) will cause the pump to lose prime. The AV21 measures the pressure on the outbound side so that the high pressure does not open the 30-50 psi switch and turn the pump off.



Xylem Inc.
 2881 East Bayard Street Ext., Suite A
 Seneca Falls, NY 13148
 Phone: (866) 325-4210
 Fax: (888) 322-5877
www.xylem.com/goulds

Goulds is a registered trademark of Goulds Pumps, Inc. and is used under license.
 © 2020 Xylem Inc. BVJ R2 May 2020